



**Review: 2013-04**

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in [www.ulmaarchitectural.com](http://www.ulmaarchitectural.com)

For more details, see technical sheets and installation guide.

### **Description**

**ULMA Polymer concrete linear drainage sump unit model AEURO100K.**

**Protective galvanized steel edge with a real thickness of 1+1mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion.**

**2 point locking bar system.**

**Load class up to C250, EN 1433 Standard.**

**Vertically and horizontally aligning tongue and groove joints.**

**CE Conformity Declaration and compliance with EN 1433 Standard.**

**Total height 315mm, internal width 100mm, total width 130mm and total length 500mm.**

**ø90mm and ø110mm pre-formed knockouts.**

**CEURO100 bucket compatible.**

**ULMA**

ARCHITECTURAL SOLUTIONS

**DRAINAGE  
SYSTEMS**

Tel.: +34 943 78 06 00  
[info@ulmaarchitectural.com](mailto:info@ulmaarchitectural.com)  
[ulmaarchitectural.com](http://ulmaarchitectural.com)