



**Review: 2013-04**

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in [www.ulmaarchitectural.com](http://www.ulmaarchitectural.com)

For more details, see technical sheets and installation guide.

### **Description**

**ULMA three unit polymer concrete sump unit model AK250S+A250I+A250B.**

**Protective galvanized steel edge with a real thickness of 2.2 mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion.**

**2 point locking bar system.**

**Load class up to C250, EN 1433 Standard.**

**Vertically and horizontally aligning tongue and groove joints.**

**CE Conformity Declaration and compliance with EN 1433 Standard.**

**Total height 1100mm, internal width 250mm, total width 312mm and total length 500mm.**

**ø160mm and ø200mm pre-formed knockouts.**

**C250 bucket compatible.**



**ARCHITECTURAL SOLUTIONS**



Tel.: +34 943 78 06 00  
[info@ulmaarchitectural.com](mailto:info@ulmaarchitectural.com)  
[ulmaarchitectural.com](http://ulmaarchitectural.com)