



Review: 2013-04

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA multIV+ Polymer concrete linear drainage sump unit model AR100G. Compatible with self-cleaning optimized V-shaped V+ section channels. Protective galvanized steel edge with a real thickness of 2+2 mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion. Boltless locking system ULMA Rapidlock®, 8 fixing points per lm. Load class up to D400, EN 1433 Standard. Vertically and horizontally aligning tongue and groove joints. CE Conformity Declaration and compliance with EN 1433 Standard. Total height 490 mm, internal width 100mm, total width 136mm and total length 500mm. \varnothing 110mm and \varnothing 160mm preformed knockouts with triple lipped seals for water tight connection. CR100 bucket compatible.

ULMA

ARCHITECTURAL SOLUTIONS

DRAINAGE SYSTEMS

Tel.: +34 943 78 06 00
info@ulmaarchitectural.com
ulmaarchitectural.com