



## FK system

External width: 362mm  
Internal width: 300mm  
Length: 1000mm

| Channel reference | Height (mm) |     | Hydraulic section (cm <sup>2</sup> ) | Ø outlet (mm) |        |
|-------------------|-------------|-----|--------------------------------------|---------------|--------|
|                   | a           | b   |                                      | Vert.         | Horiz. |
| F300K000R         | 300         | 245 | 710                                  | 250           | -      |
| F300K00R          | 390         | 335 | 975                                  | 250           | -      |
| F300K10R          | 440         | 385 | 1100                                 | 250           | -      |
| F300K20R          | 490         | 435 | 1240                                 | 250           | -      |
| F300K60R          | 600         | 545 | 1550                                 | -             | -      |

Review: 2013-10

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in [www.ulmaarchitectural.com](http://www.ulmaarchitectural.com)

For more details, see technical sheets and installation guide.

### Description

ULMA polymer concrete linear drainage channel model F300K.  
8 point bolt-locked system per lm.

Protective galvanized steel edge with a real thickness of 2+2 mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion.

Load class up to F900, EN 1433 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 362 mm, internal width 300 mm and total length 1000 mm. Total external heights available between 300 mm and 600 mm. Installation possible with no slope or stepped fall.



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00  
info@ulmaarchitectural.com  
[ulmaarchitectural.com](http://ulmaarchitectural.com)