



SELF system					
External width 312mm					
Internal width 250mm					
Length 1000mm					
Channel reference	Height (mm)		Hydraulic section (cm ²)	S outlet (mm)	
	Total	Internal		Vert.	Horiz.
SELF300K	210	167	4.07	200	-

Revizija 2019-03

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the above products is only indicative and is based on the existing technical features of the line of loading.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be valid.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guides.

Description

ULMA polymer concrete linear drainage channel model SELF300K.

Protective galvanized steel edge with a real thickness of 2+2 mm, smooth, without breakings of the protective zinc layer, avoiding water accumulation and preventing corrosion.

2 point loading bar system per lin.

Load class up to C250, EN 1439 Standard.

Vertically and horizontally channel edging: tongue and groove joints.

CE Conformity Declaration and compliance with EN 1439 Standard.

External width 312 mm, Internal width 250 mm and total length 1000 mm. Total height 210 mm.



ARCHITECTURAL SOLUTIONS



Tel: +34 949 78 04 00
 info@ulmaarchitectural.com
 ulmaarchitectural.com