



UK system

External width : 130mm
Internal width : 100mm
Length (L) : 1000mm

Channel reference	Total height		Internal height		Hydraulic section (cm ²)	Ø outlet(mm)	
	h (mm)	H (mm)	a (mm)	b (mm)		Vert.	Horz.
U100K.00R	150	150	130	130	95	110	-
U100K.01	150	155	130	135	100	-	-
U100K.02	155	160	135	140	105	-	-
U100K.03	160	165	140	145	110	-	-
U100K.04	165	170	145	150	115	-	-
U100K.05	170	175	150	155	120	-	-
U100K.05R	175	175	155	155	120	110	-
U100K.06	175	180	155	160	125	-	-
U100K.07	180	185	160	165	130	-	-
U100K.08	185	190	165	170	135	-	-
U100K.09	190	195	170	175	140	-	-

Channel reference	Total height		Internal height		Hydraulic section (cm ²)	Ø outlet(mm)	
	h (mm)	H (mm)	a (mm)	b (mm)		Vert.	Horz.
U100K.10	195	200	175	180	145	-	-
U100K.10R	200	200	180	180	145	110	110
U100K.11	200	205	180	185	150	-	-
U100K.12	205	210	185	190	155	-	-
U100K.13	210	215	190	195	159	-	-
U100K.14	215	220	195	200	164	-	-
U100K.15	220	225	200	205	169	-	-
U100K.15R	225	225	205	205	169	110	110
U100K.16	225	230	205	210	174	-	-
U100K.17	230	235	210	215	178	-	-
U100K.18	235	240	215	220	183	-	-
U100K.19	240	245	220	225	186	-	-
U100K.20	245	250	225	230	191	-	-
U100K.20R	250	250	230	230	191	110	110
U100K.25R	275	275	255	255	215	110	110
U100K.30R	300	300	280	280	240	110	110

Review: 2013-03

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA polymer concrete linear drainage channel model U100K.

Protective galvanized steel edge with a real thickness of 2x2 mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion.

2 point locking bar system per lm.

Load class up to C250, EN 1433 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 130 mm, internal width 100 mm and total height 1000 mm. Total external heights available between 150 mm y 300 mm. Installation possible with no slope, 0.5% presloped, stepped fall or mixed slope.



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00
info@ulmaarchitectural.com
ulmaarchitectural.com